clear glass & slate

SPECIFICATIONS

Name	Surface Art Clear Glass & Slate Mosaics
Colors	6: Oyster Quartz, Seashell Quartz, Pewter Rustic,
	Java Rustic, Arctic Quartz, Anthracite

Material	Glass
Sizes Available	5/8 Random Strip Mosaic on 12 x 12, 5/8 x 5/8 Mosaic on 12 x 12
Rating	Wall Only, Interior/Exterior
Variation	4

Installation Guidelines

All local building codes must be followed as well as all ANSI and TCNA guidelines (A137.2 and EJ171). Must be sealed prior to grouting.

Surface

Must be sound, stable, and free from any chance of deflection. Additional blocking may be required.

Setting Material

High performing thinset that meets or exceeds ANSI A118.4 requirements with high polymer content. Bond Strength > 400 PSI. Latex Modified thinset is sufficient.

Grout Type

A118.4 Grout must be unsanded or glass aggregate. Check packaging for opacity and water exposure guidelines. Lightly wet the surface of the glass prior to grouting to avoid grout haze.

Movement Joints

Must be placed at maximum of 8ft in all directions IAW TCNA EJ171. Flexible joint bond to be used IAW ASTM C920.

Care & Maintenance

Always clean promptly using only mild, pH-neutral detergent cleaner and damp sponge or rage. DO NOT USE acid, alkaline, solvent-based cleaners.



Ovster Ouartz, 5/8 Random Strip



Oyster Quartz, 5/8 x 5/8



Seashell Quartz, 5/8 Random Strip



eashell Ouartz, 5/8 Random Strip



Pewter Rustic, 5/8 Random Strip



Pewter Rustic, 5/8 x 5/8



Java Rustic, 5/8 Random Stri



Java Rustic, 5/8 x 5/8




Arctic Quartz, 5/8 Random Strip



Arctic Quartz, 5/8 x 5/8



Anthracite, 5/8 Random Strip



Anthracite, 5/8 x 5/8