

stone, glass, & metal micro

SPECIFICATIONS

Name Surface Art Stone, Glass, & Metal Micro Mosaics

Colors 7: Bel Air Blend, Carmel Blend, Del Mar Blend, Georgetown Blend, Sausalito Blend, Soho Blend, Tribeca Blend

Material Glass

Sizes Available 5/16 Random Strip Mosaic on 12 x 12

Rating Wall Only, Interior/Exterior

Variation 4

Installation Guidelines

All local building codes must be followed as well as all ANSI and TCNA guidelines (A137.2 and EJ171).

Surface

Must be sound, stable, and free from any chance of deflection. Additional blocking may be required.

Setting Material

High performing thinset that meets or exceeds ANSI A118.4 requirements with high polymer content. Bond Strength > 400 PSI. Latex Modified thinset is sufficient.

Grout Type

A118.4 Grout must be unsanded or glass aggregate. Check packaging for opacity and water exposure guidelines. Lightly wet the surface of the glass prior to grouting to avoid grout haze.

Movement Joints

Must be placed at maximum of 8ft in all directions IAW TCNA EJ171. Flexible joint bond to be used IAW ASTM C920.

Care & Maintenance

Always clean promptly using only mild, pH-neutral detergent cleaner and damp sponge or rag. DO NOT USE acid, alkaline, solvent-based cleaners.



Soho Blend



Del Mar Blend



Sausalito Blend



Bel Air Blend



Carmel Blend



Tribeca Blend



Georgetown Blend