translucent fresco glass

SPECIFICATIONS

Name	Surface Art Translucent Fresco Glass Mosaic
Colors	8: Brushed Bamboo, Brushed Basil,
	Brushed Carbon, Brushed Ice, Brushed Oatmeal,
	Brushed Rock, Brushed Sunset, Brushed Oxide

Material	Glass
Sizes Available	Random Mosaic on 12 x 12
Rating	Wall Only, Interior/Exterior
Variation	4

Installation Guidelines

All local building codes must be followed as well as all ANSI and TCNA guidelines (A137.2 and EJ171).

Surface

Must be sound, stable, and free from any chance of deflection. Additional blocking may be required .

Setting Material

High performing thinset that meets or exceeds ANSI A118.4 requirements with high polymer content. Bond Strength > 400 PSI. Latex Modified thinset is sufficient.

Grout Type

A118.4 Grout must be unsanded or glass aggregate. Check packaging for opacity and water exposure guidelines. Lightly wet the surface of the glass prior to grouting to avoid grout haze.

Movement Joints

Must be placed at maximum of 8ft in all directions IAW TCNA EJ171. Flexible joint bond to be used IAW ASTM C920.

Care & Maintenance

Always clean promptly using only mild, pH-neutral detergent cleaner and damp sponge or rage. DO NOT USE acid, alkaline, solvent-based cleaners.





Brushed Bamboo



Brushed Carbon



Brushed Oatmeal



Brushed Sunset




Brushed Basil



Brushed Ice



Brushed Rock



Brushed Oxide