translucent linen

SPECIFICATIONS

Name		Surface Art Translucent Linen
Colors	6: Latte Linen, Light Graphite Linen, Sand Linen Stone Linen, Taupe Linen, White Linen	
Material		Glass
Sizes Available		4 x 12 Field, 2 x 12 Field,
		Random Strip Mosaic on 6 x 18

Rating Wall Only, Interior/Exterior

Installation Guidelines

All local building codes must be followed as well as all ANSI and TCNA guidelines (A137.2 and EJ171).

Surface

Must be sound, stable, and free from any chance of deflection. Additional blocking may be required .

Setting Material

High performing thinset that meets or exceeds ANSI A118.4 requirements with high polymer content. Bond Strength > 400 PSI. Latex Modified thinset is sufficient.

Grout Type


A118.4 Grout must be unsanded or glass aggregate. Check packaging for opacity and water exposure guidelines. Lightly wet the surface of the glass prior to grouting to avoid grout haze.

Movement Joints

Must be placed at maximum of 8ft in all directions IAW TCNA EJ171. Flexible joint bond to be used IAW ASTM C920.

Care & Maintenance


Always clean promptly using only mild, pH-neutral detergent cleaner and damp sponge or rage. DO NOT USE acid, alkaline, solvent-based cleaners.



White Linen



Stone Linen



Sand Linen



Latte Linen



Taupe Linen



Light Graphite Linen