

translucent micro

SPECIFICATIONS

Name	Surface Art Translucent Micro Glass Mosaics
Colors	6: Blue Mink, Grey Mink, Latte Mink, Pearl Mink, Silver Mink, Taupe Mink
Material	Glass
Sizes Available	Mini Random Strip Mosaic on 11 x 12
Rating	Wall Only, Interior/Exterior
Variation	4

Installation Guidelines

All local building codes must be followed as well as all ANSI and TCNA guidelines (A137.2 and EJ171).

Surface

Must be sound, stable, and free from any chance of deflection. Additional blocking may be required.

Setting Material

High performing thinset that meets or exceeds ANSI A118.4 requirements with high polymer content. Bond Strength > 400 PSI. Latex Modified thinset is sufficient.

Grout Type


A118.4 Grout must be unsanded or glass aggregate. Check packaging for opacity and water exposure guidelines. Lightly wet the surface of the glass prior to grouting to avoid grout haze.

Movement Joints


Must be placed at maximum of 8ft in all directions IAW TCNA EJ171. Flexible joint bond to be used IAW ASTM C920.

Care & Maintenance


Always clean promptly using only mild, pH-neutral detergent cleaner and damp sponge or rag. DO NOT USE acid, alkaline, solvent-based cleaners.




Blue Mink



Pearl Mink



Silver Mink



Latte Mink



Grey Mink



Taupe Mink