

translucent urban glass

SPECIFICATIONS

Name	Surface Art Translucent Urban Glass
Colors	6: Light Carbon, Light Earth, Light Ice Light Mist, Light Sand, Light Smoke
Material	Glass
Sizes Available	3 x 12, 1 x 1 Mosaic on 12 x 12, 2 x 6 Brick Mosaic on 12 x 12, Random Strip Mosaic on 12 x 12
Rating	Wall Only, Interior/Exterior

Installation Guidelines

All local building codes must be followed as well as all ANSI and TCNA guidelines (A137.2 and EJ171).

Surface

Must be sound, stable, and free from any chance of deflection. Additional blocking may be required.

Setting Material

High performing thinset that meets or exceeds ANSI A118.4 requirements with high polymer content. Bond Strength > 400 PSI. Latex Modified thinset is sufficient.

Grout Type

A118.4 Grout must be unsanded or glass aggregate. Check packaging for opacity and water exposure guidelines. Lightly wet the surface of the glass prior to grouting to avoid grout haze.

Movement Joints

Must be placed at maximum of 8ft in all directions IAW TCNA EJ171. Flexible joint bond to be used IAW ASTM C920.

Care & Maintenance

Always clean promptly using only mild, pH-neutral detergent cleaner and damp sponge or rag. DO NOT USE acid, alkaline, solvent-based cleaners.



SURFACE ART



Light Carbon, Random Strip



Light Carbon, 2 x 6 Brick



Light Earth



Light Ice



Light Mist



Light Sand



Light Smoke